



SIGNBOND® LITE

Signbond® LITE is an aluminium composite signage panel. It has a robust polyethylene core bonded between two 0.15mm or 0.21mm aluminium skin suitable for flat applications. Combining strength and durability, it is ideal for outdoor signage, displays, exhibition panels. Its smooth surface ensures a flawless finish for painting or vinyl applications, while its lightweight construction makes installation quick and simple. **Signbond® LITE** is available in 2mm, 3mm and 4mm gauge sheets and also comes with a 10 year warranty.


KEY FEATURES

- 10 year warranty
- Smooth & flat surface
- Weather-resistant
- Lightweight
- Easy to cut & install

PRODUCT APPLICATIONS

- Exterior & interior signage
- POS displays
- Trade stands
- Shopfitting
- Partitions

COLOURS



Coloured swatch may not represent physical product.

PROPERTIES

GENERAL	RESULTS
Weight (3mm)	4.14kg/m ²
Relative Core Density	1.18-1.24g/cm ³
Gauge Thickness Tolerance	+/- 0.2mm
Cleaning: Warm soapy water & soft cloth	
MECHANICAL	
Shearing Strength	≥12Mpa
Bending Strength	≥50Mpa
SURFACE COATING - POLYESTER	
Thickness of Coating Average	≥16 Min ≥14
Surface	Coil Coated
Colour Variation	^E</-2.0
Gloss (Initial Value)	20-90%
Pencil Hardness	HB-F

PRODUCT RANGE

COLOUR	GAUGE	SIZE
Gloss White (0.15 Skin)	2mm	2440x1220mm
	3mm	2440x1220mm 3050x1500mm
Gloss Black Satin Black (0.21 Skin)	3mm	2440x1220mm
Gloss White (0.21 Skin)	4mm	2440x1220mm 3050x1500mm

