



SNOWBOND®

Snowbond® represents the next generation of aluminium composite panel. It has a fire-rated foamed PVC core bonded between two 0.15mm or 0.2mm aluminium skin making it ideal for lightweight commercial signage projects. **Snowbond®**'s ultra-smooth, bright white, digitally primed surface ensures brilliant ink bonding and colour output across UV, latex and screen-printing platforms. The easy-peel protective film ensures smoother and quicker handling on every project, while the panel's excellent rigidity and workability make it ideal for CNC routing, folding and 3D fabrication. It is available in 3mm and 4mm gauge sheets and also comes with a 10 year warranty.

KEY FEATURES

- 10 year warranty
- Fire-rated
- Easy-peel protective film
- Bright white, smooth & flat surface
- Weather-resistant
- Lightweight
- Easy to cut & install

PRODUCT APPLICATIONS

- Retail signage
- Digital print signage
- Commercial signage
- Interior displays
- POS displays

COLOURS



Coloured swatch may not represent physical product.

PROPERTIES

GENERAL		RESULTS
Weight - 3mm = 2.4kg/m ² 4mm = 3.3kg/m ²		
Core Density		0.6g/cm ³
Cleaning: Warm soapy water & soft cloth		
MECHANICAL		
Aluminium Grade		Alloy 1100
SURFACE COATING - POLYESTER		
Gloss Level (Digital)		25%
Flammability (EN13501-1)		Group 1S

PRODUCT RANGE

COLOUR	GAUGE	SIZE
Digital White (0.15 Skin)	3mm	2440x1220mm
Digital White (0.2 Skin)	4mm	

