



ZENOLEX[®] POLYCARBONATE

ZENOLEX[®] Polycarbonate is a high-performance extruded Polycarbonate sheet engineered for demanding architectural, signage and glazing applications. With exceptional clarity, outstanding impact resistance and UV protection, **ZENOLEX[®] Polycarbonate** provides enduring performance in harsh outdoor environments. Built for versatility, **ZENOLEX[®] Polycarbonate** is ideal for flat-sheet or thermoformed installations – From overhead glazing, security panels and machine guards to high-end displays and exterior signage. Available in a wide range of thicknesses and sheet sizes to meet almost any project requirements.

KEY FEATURES

- 10 year warranty
- Up to approximately 250 times the impact strength of glass
- UV protection both sides & weather-resistant
- Good clarity & resists yellowing
- Thermoformable & easily fabricated
- Lightweight yet rigid

PRODUCT APPLICATIONS

- Overhead & security glazing
- Skylights
- Machine guards
- Sound barriers
- Exterior & interior signage

COLOURS



Coloured swatch may not represent physical product.

PROPERTIES

GENERAL	RESULTS
Weight (3mm)	3.6kg/m ²
Relative Density (ISO1183)	1.20g/cm ³
Water Absorption (ISO62)	0.2%
Cleaning: Warm soapy water & soft cloth	
MECHANICAL	
Tensile Strength (ISO527-2)	2300Mpa
Flexural Strength (ISO178)	90Mpa
THERMAL	
Continuous Service Temperature	110°C
Vicat Softening Temp (ISO306)	135°C
Linear Thermal Expansion (DIN53752)	7/°Kx10 ⁻⁵
Flammability (ISO 9705)	Group 1S

PRODUCT RANGE

COLOUR	GAUGE	SIZE
Clear	1mm 1.5mm 2mm 10mm	2440x1220mm
	3mm 4.5mm 6mm	2440x1220mm 2440x1830mm 3050x2030mm
Cut to size available upon request		

